DEPARTMENT OF TRADE, INDUSTRY AND COMPETITION NOTICE 3481 OF 2025

STANDARDS ACT, 2008 STANDARDS MATTERS

In terms of the Standards Act, 2008 (Act No. 8 of 2008), the Board of the South African Bureau of Standards has acted in regard to standards in the manner set out in the Schedules to this notice.

SECTION A: DRAFTS FOR COMMENTS

The following draft standards are hereby issued for public comments in compliance with the norm for the development of the South Africa National standards in terms of section 23(2)(a) (ii) of the Standards Act.

Draft Standard No. and Edition	Title, scope and purport	Closing Date
SANS 15005: XXXX	Road vehicles - Ergonomic aspects of transportation and control systems -	2025-10-28
Ed 2	Dialogue management principles and compliance procedures. This standard	
	specifies ergonomic principles for the design of the dialogues that take place	
	between the driver of a road vehicle and the vehicle's transport information and	
	control systems (TICS) while the vehicle is in motion.	
SANS 20248: XXXX	Information technology - Automatic identification and data capture techniques -	2025-10-28
Ed 2 and ISO/IEC amdt 1	Data structures - Digital signature meta structure. This standards specifies the	
	meta data structure, the DigSig, which contains the digital signature and	
	encoded structured data, the public key certificate parameter and extension use,	
	the DigSig certificate, which contains the certified associated public key, the	
	structured data description, the read methods, and private containers, the	
	method to specify, read, describe, sign, verify, encode, and decode the	
	structured data, the DigSig Data Description, the DigSig EncoderGenerator	
	which generates the relevant asymmetric key pairs, keeps the private key secret,	
	and generates the DigSigs, and the DigSig DecoderVerifier which, by using to	
	the DigSig certificate, reads the DigSig from the set of data carriers, verifies the	
	DigSig and extracts the structured data from the DigSig.	
SANS 457-3: 202X	Wooden poles, droppers and guardrail posts - Part 3: Hardwood species. This	2025-10-28
Ed 9	standard specifies requirements for preservative-treated hardwood structural	
	poles, agricultural poles, fencing poles, round droppers, guardrail posts and	
	spacer blocks.	
SATS 62840-1: XXXXXX	Electric vehicle battery swap system -Part 1: General and guidance. This	2025-10-28
Ed 1	standard gives the general overview for battery swap systems, for the purposes	
	of swapping batteries of electric road vehicles (EVs)	
	when the vehicle powertrain is turned off and when the battery swap system is	
	connected to the supply network at standard supply voltages according to IEC	
	60038 with a rated voltage up to 1 000 V AC and up to 1 500 V DC. This	
	document is applicable for battery swap systems for EV equipped with one or	
	more swappable battery system (SBS).	
SANS 15118-9:XXXXX	Road vehicles - Vehicle to grid communication interface - Part 9: Physical and	2025-10-28
Ed 1	data link layer conformance test for wireless communication. This document	
	specifies conformance tests in the form of an abstract test suite (ATS) for a	
	system under test (SUT) implementing an electric-vehicle or supply-equipment	
	communication controller (EVCC or SECC) with support for WLAN-based	
	high-level communication (HLC) according to ISO 15118-8 and against the	
	background of ISO 15118-1. These conformance tests specify the testing of	
	capabilities and behaviours of an SUT, as well as checking what is observed	
	against the conformance requirements specified in ISO 15118-8 and against	
	what the implementer states the SUT implementation's capabilities	
	are. The capability tests within the ATS check that the observable capabilities of	

the SUT are in accordance with the static conformance requirements defined in ISO 15118-8. The behaviour tests of the ATS examine an implementation as thoroughly as practical over the full range of dynamic conformance requirements fedined in ISO 15118-8 and within the capabilities of the SUT (see NOTE below). A test architecture is described in correspondence to the ATS. The abstract test cases in this document are described leveraging this test architecture and are specified in descriptive tabular format for the ISO/OSI physical and data link layers (layers) and 2). SANS 61980-2: XXXXXX Ed 1 SANS 61980-2: XXXXXX Ed 1 Ed 1 SANS 61980-3: XXXXXXX Ed 1 SANS 61980-3: XXXXXXX Ed 1 Requirements for MF-WFT system communication and activities. This part of IEC 61980 addresses communication and activities of Impension of the WF-WFT communication systems and related activities, and Operational and functional characteristics of the positioning system. The following aspects are under consideration for future documents. Requirements for MF-WFT systems supplying power to EVs in monitors. Electric vehicle wireless power transfer of the positioning system. The following aspects are under consideration for future documents. Requirements for MF-WFT systems supplying power to EVs in monitors. Electric vehicle wireless power transfer of the positioning system. Electric vehicle wireless power transfer of the positioning system. Electric vehicle wireless power transfer of the positioning systems of the Co1980 applies to the off-board apply equipment for wireless power transfer via magnetic field fwireless power transfer via magnetic field (MF-WFT) systems systems. This part of IEC 61980 applies to the off-board apply equipment for wireless power transfer via magnetic field wireless power transfer via magnetic field wireless power transfer via magnetic field wireless power transfer systems. This part of IEC 61980 applies to the off-board apply equipment fuffilling the requirements for wireless of the purposes of su			
Electric vehicle wireless power transfer (WPT) systems -Part 2: Specific requirements for Mr-WPT system communication and activities. This part of IEC 61980 addresses communication and activities of magnetic field wireless power transfer (Mr-WPT) systems. The requirements in this document are intended to be applied for MF-WPT systems according to IEC 61980-3 and ISO 19363. The aspects overed in this document include - Operational and functional characteristics of the positioning system. The following aspects are under consideration for future documents. - Requirements for two- and three-wheel vehicles; - Requirements for two- and three-wheel vehicles; - Requirements for bidirectional power transfer. SANS 61980-3: XXXXXX Electric vehicle wireless power transfer (WPT) systems -Part 3: Specific requirements for magnetic field wireless power transfer systems. This part of IEC 61980 applies to the off-board supply equipment for wireless power transfer via magnetic field (Mr-WPT) to electric road vehicles for purposes of supplying electric energy to the RESS (rechargeable energy storage system) and/or other on-board electrical systems. The Mr-WPT system operates at standard supply voltage ratings per IEC 60038 up to 1 000 V AC and up to 1 500 V DC from the supply network. The power transfer kess place while the electric vehicle (EV) is stationary. Off-board supply equipment fulfilling the requirements in this document are intended to operate with EV devices fulfilling the requirements for basic communication for safety and process matters if requirements for basic communication for safety and process matters if requirements for basic communication for future documents: - requirements for Positioning to assure efficient and safe MF-WPT power transfer, requirements for MF-WPT systems rotwo- and three-wheel vehicles, requirements for MF-WPT systems supplying power to EVs in motion, requirements for MF-WPT systems supplying power to EVs in motion, requirements for MF-WPT systems for two- and three-wheel vehicles,		ISO 15118-8. The behaviour tests of the ATS examine an implementation as thoroughly as practical over the full range of dynamic conformance requirements defined in ISO 15118-8 and within the capabilities of the SUT (see NOTE below). A test architecture is described in correspondence to the ATS. The abstract test cases in this document are described leveraging this test architecture and are specified in descriptive tabular format for the ISO/OSI physical and data link	
IEC 6 1980 addresses communication and activities of magnetic field wireless power transfer (MF-WPT) systems. The requirements in this document are intended to be applied for MF-WPT systems according to IEC 61980-3 and ISO 19363. The aspects covered in this document include Operational and functional characteristics of the MF-WPT communication systems and related activities, and Operational and functional characteristics of the positioning system. The following aspects are under consideration for future documents. Requirements for two- and three-wheel vehicles; Requirements for bidirectional power transfer. Ed 1 Ed 1 Ed 1 Ed 1 Edectric vehicle wireless power transfer (WPD) systems -Part 3: Specific requirements for magnetic field wireless power transfer systems. This part of IEC 61980 applies to the off-board supply college for proposes of supplying electric energy to the RESS (rechargeable energy storage system) and/or other on-board electrical systems. The MF-WPT system operates at standard supply voltage ratings per IEC 60038 up to 1 000 V AC and up to 1 500 V DC from the supply network. The power transfer takes place while the electric vehicle (EV) is stationary. Off-board supply equipment fulfilling the requirements in this document are intended to operate with EV devices fulfilling the requirements described in ISO 19363. The aspects covered in this document include - the characteristics and operating conditions, - the required by a MF-WPT system requirements for basic communication for safety and process matters if required by a MF-WPT systems. The following aspects are under consideration for future documents: - requirements for MF-WPT systems supplying power to EVs in motion, - requirements for MF-WPT systems sor heavy duty vehicle, and - requirements for	SANS 61980-2: XXXXX		2025-10-28
- Operational and functional characteristics of the positioning system. The following aspects are under consideration for future documents. - Requirements for two- and three-wheel vehicles; - Requirements for two- and three-wheel vehicles; - Requirements for MF-WPT systems supplying power to EVs in motion; - Requirements for bidirectional power transfer. - Requirements for misches power transfer (WPT) systems - Part 3: Specific requirements for magnetic field wireless power transfer systems. This part of IEC 61980 applies to the off-board supply equipment for wireless power transfer it amagnetic field (MF-WPT) to electric road vehicles for purposes of supplying electric energy to the RESS (rechargeable energy storage system) and/or other on-board electrical systems. The MF-WPT system operates at standard supply voltage ratings per IEC 60038 up to 1 000 V AC and up to 1 500 V DC from the supply network. The power transfer takes place while the electric vehicle (EV) is stationary. Off-board supply equipment fulfilling the requirements in this document are intended to operate with EV devices fulfilling the requirements described in ISO 1936. The aspects covered in this document include - the characteristics and operating conditions, - the required level of electrical safety, - requirements for basic communication for safety and process matters if required by a MF-WPT system, - requirements for positioning to assure efficient and safe MF-WPT power transfer, and - specific EMC requirements for MF-WPT systems. The following aspects are under consideration for future documents: - requirements for MF-WPT systems for two- and three-wheel vehicles, - requirements for MF-WPT systems supplying power to EVs in motion, - requirements for MF-WPT systems with inputs greater than 11,1 kVA. This document does not apply to - safety aspects related to maintenance, and - trolley buses, rail vehicles and vehicles designed primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT Electric veh	Ed 1	IEC 61980 addresses communication and activities of magnetic field wireless power transfer (MF-WPT) systems. The requirements in this document are intended to be applied for MF-WPT systems according to IEC 61980-3 and ISO 19363. The aspects covered in this document include - Operational and functional characteristics of the MF-WPT	
The following aspects are under consideration for future documents. Requirements for two- and three-wheel vehicles; Requirements for two- and three-wheel vehicles; Requirements for bidirectional power transfer. Ed 1 Ed 1980 applies to the off-board supply equipment for wireless power transfer via magnetic field (MF-WPT) to electric road vehicles for purposes of supplying electric energy to the RESS (rechargeable energy storage system) and/or other on-board electrical systems. The MF-WPT system operates at standard supply voltage ratings per IEC 60038 up to 1 000 V AC and up to 1 500 V DC from the supply network. The power transfer takes place while the electric vehicle (EV) is stationary. Off-board supply equipment fulfilling the requirements in this document are intended to operate with EV devices fulfilling the requirements is this Acument are intended to operate with EV devices fulfilling the requirements sees ribed in ISO 19363. The aspects covered in this document include - the characteristics and operating conditions, - the required level of electrical safety, - requirements for basic communication for safety and process matters if required by a MF-WPT system, - requirements for positioning to assure efficient and safe MF-WPT power transfer, and - specific EMC requirements for MF-WPT systems. The following aspects are under consideration for future documents: - requirements for MF-WPT systems for two- and three-wheel vehicles, - requirements for MF-WPT systems for heavy duty vehicle, and - requirements for MF-WPT systems for heavy duty vehicle, and - requirements for MF-WPT systems for heavy duty vehicle, and - requirements for MF-WPT systems for heavy duty vehicle, and - requirements for MF-WPT systems for heavy duty vehicle, and - requirements for MF-WPT systems for heavy duty vehicle, and - requirements for high the future of the supply system for the purposes of swapping swappable battery system for but purposes of swapping swappable battery system for			
- Requirements for two- and three-wheel vehicles; - Requirements for MF-WPT systems supplying power to EVs in motion; - Requirements for bidirectional power transfer. SANS 61980-3: XXXXXX Ed 1 Electric vehicle wireless power transfer (WPT) systems -Part 3: Specific requirements for magnetic field wireless power transfer systems. This part of IEC 61980 applies to the off-board supply equipment for wireless power transfer via magnetic field (MF-WPT) to electric road vehicles for purposes of supplying electric energy to the RESS (rechargeable energy storage system) and/or other on-board electrical systems. The MF-WPT system operates at standard supply voltage ratings per IEC 60038 up to 1 000 V AC and up to 1 500 V DC from the supply network. The power transfer takes place while the electric vehicle (EV) is stationary. Off-board supply equipment fulfilling the requirements in this document are intended to operate with EV devices fulfilling the requirements described in ISO 1936. The aspects covered in this document include - the characteristics and operating conditions, - the required by a MF-WPT system, - requirements for basic communication for safety and process matters if required by a MF-WPT system, - requirements for positioning to assure efficient and safe MF-WPT power transfer, and - specific EMC requirements for MF-WPT systems. The following aspects are under consideration for future documents: - requirements for MF-WPT systems for two- and three-wheel vehicles, - requirements for MF-WPT systems for two- and three-wheel vehicles, - requirements for MF-WPT systems for heavy duty vehicle, and - requirements for MF-WPT systems with inputs greater than 11,1 kVA. This document does not apply to - safety aspects related to maintenance, and - trolley buses, rail vehicles and vehicles designed primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT Electric vehicle battery swap system - Part 2: Safety requirements. This part of IEC 62840 provides the safety requirement			
motion; - Requirements for bidirectional power transfer. SANS 61980-3: XXXXXX Ed 1 Electric vehicle wireless power transfer (WPT) systems -Part 3: Specific requirements for magnetic field wireless power transfer systems. This part of IEC 61980 applies to the off-board supply equipment for wireless power transfer via magnetic field (MF-WPT) to electric road vehicles for purposes of supplying electric energy to the RESS (rechargeable energy storage system) and/or other on-board electrical systems. The MF-WPT system operates at standard supply voltage ratings per IEC 60038 up to 1 000 V AC and up to 1 500 V DC from the supply network. The power transfer takes place while the electric vehicle (EV) is stationary. Off-board supply equipment fulfilling the requirements in this document are intended to operate with EV devices fulfilling the requirements described in ISO 19363. The aspects covered in this document include - the characteristics and operating conditions, - the required level of electrical safety, - requirements for basic communication for safety and process matters if required by a MF-WPT system requirements for positioning to assure efficient and safe MF-WPT power transfer, and - specific EMC requirements for MF-WPT systems. The following aspects are under consideration for future documents: - requirements for MF-WPT systems supplying power to EVs in motion, - requirements for MF-WPT systems supplying power to EVs in motion, - requirements for bidirectional power transfer, - requirements for MF-WPT systems with inputs greater than 11,1 kVA. This document does not apply to - safety aspects related to maintenance, and - trolley buses, rail vehicles and vehicles designed primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT Electric vehicle battery swap system -Part 2: Safety requirements. This part of IEC 62840 provides the safety requirements for battery swap system, for the purposes of swapping swappable battery system (sbs) of electric vehicles. The batt		- Requirements for two- and three-wheel vehicles;	
Ed 1 Ed 1 Ed 1 Electric vehicle wireless power transfer (WPT) systems -Part 3: Specific requirements for magnetic field wireless power transfer systems. This part of IEC 61980 applies to the off-board supply equipment for wireless power transfer via magnetic field (MF-WPT) to electric road vehicles for purposes of supplying electric energy to the RESS (rechargeable energy storage system) and/or other on-board electrical systems. The MF-WPT system operates at standard supply voltage ratings per IEC 60038 up to 1 000 V AC and up to 1 500 V DC from the supply network. The power transfer takes place while the electric vehicle (EV) is stationary. Off-board supply equipment fulfilling the requirements in this document are intended to operate with EV devices fulfilling the requirements described in ISO 19363. The aspects covered in this document include - the characteristics and operating conditions, - the required level of electrical safety, - requirements for basic communication for safety and process matters if required by a MF-WPT system, - requirements for PS-WPT systems. The following aspects are under consideration for future documents: - requirements for MF-WPT systems for two- and three-wheel vehicles, - requirements for MF-WPT systems for two- and three-wheel vehicles, - requirements for MF-WPT systems for two- and three-wheel vehicles, - requirements for MF-WPT systems with inputs greater than 11,1 kVA. This document does not apply to - safety aspects related to maintenance, and - trolley buses, rail vehicles and epithemical primary device, - requirements for MF-WPT systems with inputs greater than 11,1 kVA. This document does not apply to - safety aspects related to maintenance, and - trolley buses, rail vehicles and seigned primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT Edectric vehicle battery swap system -Part 2: Safety requirements. This part of IEC 62840 provides the safety requirements for a battery swap system, for the purposes of swapping swappa		motion;	
requirements for magnetic field wireless power transfer systems. This part of IEC 61980 applies to the off-board supply equipment for wireless power transfer via magnetic field (MF-WPT) to electric road vehicles for purposes of supplying electric energy to the RESS (rechargeable energy storage system) and/or other on-board electrical systems. The MF-WPT system operates at standard supply voltage ratings per IEC 60038 up to 1 000 V AC and up to 1 500 V DC from the supply network. The power transfer takes place while the electric vehicle (EV) is stationary. Off-board supply equipment fulfilling the requirements in this document are intended to operate with EV devices fulfilling the requirements described in ISO 19363. The aspects covered in this document include - the characteristics and operating conditions, - the required level of electrical safety, - requirements for basic communication for safety and process matters if required by a MF-WPT system, - requirements for basic communication for safety and process matters if required by a MF-WPT system, - requirements for MF-WPT systems. The following aspects are under consideration for future documents: - requirements for MF-WPT systems for two- and three-wheel vehicles, - requirements for MF-WPT systems supplying power to EVs in motion, - requirements for MF-WPT systems for two- and three-wheel vehicles, - requirements for MF-WPT systems with inputs greater than 11,1 kVA. This document does not apply to - safety aspects related to maintenance, and - trolley buses, rail vehicles and vehicles designed primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT Electric vehicle battery swap system -Part 2: Safety requirements. This part of IEC 62840 provides the safety requirements for a battery swap system, for the purposes of swapping swappable battery system (sbs) of electric vehicles. The battery swap system is intended to be connected to the supply network. The power supply is uo to 1 000 V AC or up to 1 500 V d.e., in accor	SANS 61080-3: YYYYYY	- Requirements for bidirectional power transfer. Flactric vahiela wireless power transfer (WPT) systems -Part 3: Specific	2025_10_28
IEC 61980 applies to the off-board supply equipment for wireless power transfer via magnetic field (MF-WPT) to electric road vehicles for upposes of supplying electric energy to the RESS (rechargeable energy storage system) and/or other on-board electrical systems. The MF-WPT system operates at standard supply voltage ratings per IEC 60038 up to 1 000 V AC and up to 1 500 V DC from the supply network. The power transfer takes place while the electric vehicle (EV) is stationary. Off-board supply equipment fulfilling the requirements in this document are intended to operate with EV devices fulfilling the requirements described in ISO 19363. The aspects covered in this document include — the characteristics and operating conditions, — the requirements for basic communication for safety and process matters if required level of electrical safety, — requirements for basic communication for safety and process matters if required by a MF-WPT system, — requirements for positioning to assure efficient and safe MF-WPT power transfer, and — specific EMC requirements for MF-WPT systems. The following aspects are under consideration for future documents: — requirements for MF-WPT systems for two- and three-wheel vehicles, — requirements for MF-WPT systems supplying power to EVs in motion, — requirements for MF-WPT systems for two- and three-wheel vehicles, — requirements for flush mounted primary device, — requirements for MF-WPT systems with inputs greater than 11,1 kVA. This document does not apply to — safety aspects related to maintenance, and — trolley buses, rail vehicles and vehicles designed primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT Electric wehicle battery swap system supplied from on-site storage systems is intended to be connected to the supply network. The power supply is uo to 1 000 V AC or up to 1 500 V d.c., in accordance with IEC 60038. This standard also applies to battery swap systems supplied from on-site storage systems (e.g. buffer batteries). Aspec			2023-10-20
supplying electric energy to the RESS (rechargeable energy storage system) and/or other on-board electrical systems. The MF-WPT system operates at standard supply voltage ratings per IEC 60038 up to 1 000 V AC and up to 1 500 V DC from the supply network. The power transfer takes place while the electric vehicle (EV) is stationary. Off-board supply equipment fillfilling the requirements in this document are intended to operate with EV devices fulfilling the requirements document are intended to operate with EV devices fulfilling the requirements document include - the characteristics and operating conditions, - the required level of electrical safety, - requirements for basic communication for safety and process matters if required by a MF-WPT system, - requirements for positioning to assure efficient and safe MF-WPT power transfer, and - specific EMC requirements for MF-WPT systems. The following aspects are under consideration for future documents: - requirements for MF-WPT systems supplying power to EVs in motion, - requirements for MF-WPT systems supplying power to EVs in motion, - requirements for bidirectional power transfer, - requirements for MF-WPT systems with inputs greater than 11,1 kVA. This document does not apply to - safety aspects related to maintenance, and - trolley buses, rail vehicles and vehicles designed primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT SANS 62840-2:XXXXX Electric vehicle battery swap system - Part 2: Safety requirements. This part of IEC 62840 provides the safety requirements for a battery swap system, for the purposes of swapping swappable battery system (sels) of electric vehicles. The battery swap system is intended to be connected to the supply network. The powere supply is uo to 1 000 V AC or up to 1 500 V d.c, in accordance with IEC 60038. This standard also applies to battery swap system and/or its systems; - Safety requirements of the battery swap system and/or its systems;			
and/or other on-board electrical systems. The MF-WPT system operates at standard supply voltage ratings per IEC 60038 up to 1 000 V AC and up to 1 500 V DC from the supply network. The power transfer takes place while the electric vehicle (EV) is stationary. Off-board supply equipment fulfilling the requirements in this document are intended to operate with EV devices fulfilling the requirements described in ISO 19363. The aspects covered in this document include - the characteristics and operating conditions, - the required level of electrical safety, - requirements for basic communication for safety and process matters if required by a MF-WPT system, - requirements for positioning to assure efficient and safe MF-WPT power transfer, and - specific EMC requirements for MF-WPT systems. The following aspects are under consideration for future documents: - requirements for MF-WPT systems supplying power to EVs in motion, - requirements for MF-WPT systems supplying power to EVs in motion, - requirements for flush mounted primary device, - requirements for MF-WPT systems with inputs greater than 11,1 kVA. This document does not apply to - safety aspects related to maintenance, and - trolley buses, rail vehicles and vehicles designed primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT SANS 62840-2:XXXXX Ed 1 Electric vehicle battery swap system -Part 2: Safety requirements. This part of IEC 62840 provides the safety requirements for a battery swap system, for the purposes of swapping swappable battery system (sbs) of electric vehicles. The battery swap system is intended to be connected to the supply network. The powere supply is uo to 1 000 V AC or up to 1 500 V d.c., in accordance with IEC 60038. This standard also applies to battery swap systems supplied from on-site storage systems (e.g. buffer batteries). Aspects covered in this standard: • Safety requirements of the battery swap system and/or its systems;			
standard supply voltage ratings per IEC 60038 up to 1 000 V AC and up to 1 500 V DC from the supply network. The power transfer takes place while the electric vehicle (EV) is stationary. Off-board supply equipment fulfilling the requirements in this document are intended to operate with EV devices fulfilling the requirements described in ISO 19363. The aspects covered in this document include - the characteristics and operating conditions, - the required level of electrical safety, - requirements for basic communication for safety and process matters if required by a MF-WPT system, - requirements for positioning to assure efficient and safe MF-WPT power transfer, and - specific EMC requirements for MF-WPT systems. The following aspects are under consideration for future documents: - requirements for MF-WPT systems supplying power to EVs in motion, - requirements for MF-WPT systems supplying power to EVs in motion, - requirements for bidirectional power transfer, - requirements for Brand mounted primary device, - requirements for MF-WPT systems with inputs greater than 11,1 kVA. This document does not apply to - safety aspects related to maintenance, and - trolley buses, rail vehicles and vehicles designed primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT SANS 62840-2:XXXXX Ed 1 Electric vehicle battery swap system - Safety requirements. This part of IEC 62840 provides the safety requirements for a battery swap system, for the purposes of swapping swappable battery system (sbs) of electric vehicles. The battery swap system si intended to be connected to the supply network. The powere supply is uo to 1 000 V AC or up to 1 500 V d.c, in accordance with IEC 60038. This standard also applies to battery swap systems supplied from on-site storage systems (e.g. buffer battery swap systems supplied from on-site storage systems (e.g. buffer battery swap system and/or its systems;			
500 V DC from the supply network. The power transfer takes place while the electric vehicle (EV) is stationary. Off-board supply equipment fulfilling the requirements in this document are intended to operate with EV devices fulfilling the requirements described in ISO 19363. The aspects covered in this document include - the characteristics and operating conditions, - the required level of electrical safety, - requirements for basic communication for safety and process matters if required by a MF-WPT system, - requirements for positioning to assure efficient and safe MF-WPT power transfer, and - specific EMC requirements for MF-WPT systems. The following aspects are under consideration for future documents: - requirements for MF-WPT systems supplying power to EVs in motion, - requirements for MF-WPT systems supplying power to EVs in motion, - requirements for MF-WPT systems proposed to EVs in motion, - requirements for Instructional power transfer, - requirements for MF-WPT systems with inputs greater than 11,1 kVA. This document does not apply to - safety aspects related to maintenance, and - trolley buses, rail vehicles and vehicles designed primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT SANS 62840-2:XXXXX Ed 1 Electric vehicle battery swap system -Part 2: Safety requirements. This part of IEC 62840 provides the safety requirements for a battery swap system, for the purposes of swapping swappable battery system (sbs) of electric vehicles. The battery swap system is intended to be connected to the supply network. The powere supply is uo to 1 000 V AC or up to 1 500 V d.c, in accordance with IEC 60038. This standard also applies to battery swap systems supplied from on-site storage systems (e.g. buffer batteries). Aspects covered in this standard: • Safety requirements of the battery swap system and/or its systems;			
electric vehicle (EV) is stationary. Off-board supply equipment fulfilling the requirements in this document are intended to operate with EV devices fulfilling the requirements described in ISO 19363. The aspects covered in this document include the characteristics and operating conditions, the required level of electrical safety, requirements for basic communication for safety and process matters if required by a MF-WPT system, requirements for positioning to assure efficient and safe MF-WPT power transfer, and specific EMC requirements for MF-WPT systems. The following aspects are under consideration for future documents: requirements for MF-WPT systems for two- and three-wheel vehicles, requirements for MF-WPT systems supplying power to EVs in motion, requirements for MF-WPT systems supplying power to EVs in motion, requirements for MISH mounted primary device, requirements for MF-WPT systems with inputs greater than 11,1 kVA. This document does not apply to safety aspects related to maintenance, and trolley buses, rail vehicles and vehicles designed primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT SANS 62840-2:XXXXX Ed 1 Electric vehicle battery swap system -Part 2: Safety requirements. This part of IEC 62840 provides the safety requirements for a battery swap system, for the purposes of swapping swappable battery system (sbs) of electric vehicles. The battery swap system is intended to be connected to the supply network. The powere supply is uo to 1 000 V AC or up to 1 500 V d.c., in accordance with IEC 60038. This standard also applies to battery swap systems supplied from on-site storage systems (e.g. buffer batteries). Aspects covered in this standard: Safety requirements of the battery swap system and/or its systems;			
include - the characteristics and operating conditions, - the required level of electrical safety, - requirements for basic communication for safety and process matters if required by a MF-WPT system, - requirements for positioning to assure efficient and safe MF-WPT power transfer, and - specific EMC requirements for MF-WPT systems. The following aspects are under consideration for future documents: - requirements for MF-WPT systems for two- and three-wheel vehicles, - requirements for MF-WPT systems supplying power to EVs in motion, - requirements for flush mounted primary device, - requirements for flush mounted primary device, - requirements for MF-WPT systems for heavy duty vehicle, and - requirements for MF-WPT systems with inputs greater than 11,1 kVA. This document does not apply to - safety aspects related to maintenance, and - trolley buses, rail vehicles and vehicles designed primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT SANS 62840-2:XXXXX Electric vehicle battery swap system -Part 2: Safety requirements. This part of IEC 62840 provides the safety requirements for a battery swap system, for the purposes of swapping swappable battery system (sbs) of electric vehicles. The battery swap system is intended to be connected to the supply network. The powere supply is uo to 1 000 V AC or up to 1 500 V d.c, in accordance with IEC 60038. This standard also applies to battery swap system supplied from on-site storage systems (e.g. buffer batteries). Aspects covered in this standard: • Safety requirements of the battery swap system and/or its systems;		electric vehicle (EV) is stationary. Off-board supply equipment fulfilling the	
- the characteristics and operating conditions, - the required level of electrical safety, - the requirements for basic communication for safety and process matters if required by a MF-WPT system, - requirements for positioning to assure efficient and safe MF-WPT power transfer, and - specific EMC requirements for MF-WPT systems. The following aspects are under consideration for future documents: - requirements for MF-WPT systems for two- and three-wheel vehicles, - requirements for MF-WPT systems supplying power to EVs in motion, - requirements for bidirectional power transfer, - requirements for flush mounted primary device, - requirements for MF-WPT systems for heavy duty vehicle, and - requirements for MF-WPT systems with inputs greater than 11,1 kVA. This document does not apply to - safety aspects related to maintenance, and - trolley buses, rail vehicles and vehicles designed primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT SANS 62840-2:XXXXX Ed 1 Electric vehicle battery swap system -Part 2: Safety requirements. This part of IEC 62840 provides the safety requirements for a battery swap system, for the purposes of swapping swappable battery system (sbs) of electric vehicles. The battery swap system is intended to be connected to the supply network. The powere supply is uo to 1 000 V AC or up to 1 500 V d.c, in accordance with IEC 60038. This standard also applies to battery swap system supplied from on-site storage systems (e.g. buffer batteries). Aspects covered in this standard: • Safety requirements of the battery swap system and/or its systems;		-	
- the required level of electrical safety, - requirements for basic communication for safety and process matters if required by a MF-WPT system, - requirements for positioning to assure efficient and safe MF-WPT power transfer, and - specific EMC requirements for MF-WPT systems. The following aspects are under consideration for future documents: - requirements for MF-WPT systems for two- and three-wheel vehicles, - requirements for MF-WPT systems supplying power to EVs in motion, - requirements for bidirectional power transfer, - requirements for flush mounted primary device, - requirements for MF-WPT systems with inputs greater than 11,1 kVA. This document does not apply to - safety aspects related to maintenance, and - trolley buses, rail vehicles and vehicles designed primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT SANS 62840-2:XXXXX Ed 1 Electric vehicle battery swap system -Part 2: Safety requirements. This part of IEC 62840 provides the safety requirements for a battery swap system, for the purposes of swapping swappable battery system (sbs) of electric vehicles. The battery swap system is intended to be connected to the supply network. The powere supply is uo to 1 000 V AC or up to 1 500 V d.c, in accordance with IEC 60038. This standard also applies to battery swap systems supplied from on-site storage systems (e.g. buffer batteries). Aspects covered in this standard: • Safety requirements of the battery swap system and/or its systems;			
- requirements for basic communication for safety and process matters if required by a MF-WPT system, - requirements for positioning to assure efficient and safe MF-WPT power transfer, and - specific EMC requirements for MF-WPT systems. The following aspects are under consideration for future documents: - requirements for MF-WPT systems for two- and three-wheel vehicles, - requirements for MF-WPT systems supplying power to EVs in motion, - requirements for fulsh mounted primary device, - requirements for fulsh mounted primary device, - requirements for MF-WPT systems for heavy duty vehicle, and - requirements for MF-WPT systems with inputs greater than 11,1 kVA. This document does not apply to - safety aspects related to maintenance, and - trolley buses, rail vehicles and vehicles designed primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT Electric vehicle battery swap system -Part 2: Safety requirements. This part of IEC 62840 provides the safety requirements for a battery swap system, for the purposes of swapping swappable battery system (sbs) of electric vehicles. The battery swap system is intended to be connected to the supply network. The powere supply is uo to 1 000 V AC or up to 1 500 V d.c, in accordance with IEC 60038. This standard also applies to battery swap systems supplied from on-site storage systems (e.g. buffer batteries). Aspects covered in this standard: • Safety requirements of the battery swap system and/or its systems;			
required by a MF-WPT system, requirements for positioning to assure efficient and safe MF-WPT power transfer, and specific EMC requirements for MF-WPT systems. The following aspects are under consideration for future documents: requirements for MF-WPT systems for two- and three-wheel vehicles, requirements for MF-WPT systems supplying power to EVs in motion, requirements for bidirectional power transfer, requirements for MF-WPT systems for heavy duty vehicle, and requirements for MF-WPT systems with inputs greater than 11,1 kVA. This document does not apply to safety aspects related to maintenance, and trolley buses, rail vehicles and vehicles designed primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT SANS 62840-2:XXXXX Ed 1 Electric vehicle battery swap system -Part 2: Safety requirements. This part of IEC 62840 provides the safety requirements for a battery swap system, for the purposes of swapping swappable battery system (sbs) of electric vehicles. The battery swap system is intended to be connected to the supply network. The power supply is uo to 1 000 V AC or up to 1 500 V d.c, in accordance with IEC 60038. This standard also applies to battery swap systems supplied from on-site storage systems (e.g. buffer batteries). Aspects covered in this standard: Safety requirements of the battery swap system and/or its systems;			
transfer, and - specific EMC requirements for MF-WPT systems. The following aspects are under consideration for future documents: - requirements for MF-WPT systems for two- and three-wheel vehicles, - requirements for MF-WPT systems supplying power to EVs in motion, - requirements for bidirectional power transfer, - requirements for flush mounted primary device, - requirements for MF-WPT systems for heavy duty vehicle, and - requirements for MF-WPT systems with inputs greater than 11,1 kVA. This document does not apply to - safety aspects related to maintenance, and - trolley buses, rail vehicles and vehicles designed primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT SANS 62840-2:XXXXX Ed 1 Electric vehicle battery swap system -Part 2: Safety requirements. This part of IEC 62840 provides the safety requirements for a battery swap system, for the purposes of swapping swappable battery system (sbs) of electric vehicles. The battery swap system is intended to be connected to the supply network. The powere supply is uo to 1 000 V AC or up to 1 500 V d.c., in accordance with IEC 60038. This standard also applies to battery swap systems supplied from on-site storage systems (e.g. buffer batteries). Aspects covered in this standard: • Safety requirements of the battery swap system and/or its systems;			
- specific EMC requirements for MF-WPT systems. The following aspects are under consideration for future documents: - requirements for MF-WPT systems for two- and three-wheel vehicles, - requirements for MF-WPT systems supplying power to EVs in motion, - requirements for bidirectional power transfer, - requirements for flush mounted primary device, - requirements for MF-WPT systems for heavy duty vehicle, and - requirements for MF-WPT systems with inputs greater than 11,1 kVA. This document does not apply to - safety aspects related to maintenance, and - trolley buses, rail vehicles and vehicles designed primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT SANS 62840-2:XXXXX Ed 1 Electric vehicle battery swap system -Part 2: Safety requirements. This part of IEC 62840 provides the safety requirements for a battery swap system, for the purposes of swapping swappable battery system (sbs) of electric vehicles. The battery swap system is intended to be connected to the supply network. The powere supply is uo to 1 000 V AC or up to 1 500 V d.c, in accordance with IEC 60038. This standard also applies to battery swap systems supplied from on-site storage systems (e.g. buffer batteries). Aspects covered in this standard: • Safety requirements of the battery swap system and/or its systems;			
The following aspects are under consideration for future documents: - requirements for MF-WPT systems for two- and three-wheel vehicles, - requirements for MF-WPT systems supplying power to EVs in motion, - requirements for bidirectional power transfer, - requirements for flush mounted primary device, - requirements for MF-WPT systems for heavy duty vehicle, and - requirements for MF-WPT systems with inputs greater than 11,1 kVA. This document does not apply to - safety aspects related to maintenance, and - trolley buses, rail vehicles and vehicles designed primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT SANS 62840-2:XXXXX Electric vehicle battery swap system -Part 2: Safety requirements. This part of IEC 62840 provides the safety requirements for a battery swap system, for the purposes of swapping swappable battery system (sbs) of electric vehicles. The battery swap system is intended to be connected to the supply network. The powere supply is uo to 1 000 V AC or up to 1 500 V d.c, in accordance with IEC 60038. This standard also applies to battery swap systems supplied from on-site storage systems (e.g. buffer batteries). Aspects covered in this standard: • Safety requirements of the battery swap system and/or its systems;			
- requirements for MF-WPT systems supplying power to EVs in motion, - requirements for bidirectional power transfer, - requirements for flush mounted primary device, - requirements for MF-WPT systems for heavy duty vehicle, and - requirements for MF-WPT systems with inputs greater than 11,1 kVA. This document does not apply to - safety aspects related to maintenance, and - trolley buses, rail vehicles and vehicles designed primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT SANS 62840-2:XXXXX Electric vehicle battery swap system -Part 2: Safety requirements. This part of IEC 62840 provides the safety requirements for a battery swap system, for the purposes of swapping swappable battery system (sbs) of electric vehicles. The battery swap system is intended to be connected to the supply network. The powere supply is uo to 1 000 V AC or up to 1 500 V d.c, in accordance with IEC 60038. This standard also applies to battery swap systems supplied from on-site storage systems (e.g. buffer batteries). Aspects covered in this standard: • Safety requirements of the battery swap system and/or its systems;			
- requirements for bidirectional power transfer, - requirements for flush mounted primary device, - requirements for MF-WPT systems for heavy duty vehicle, and - requirements for MF-WPT systems with inputs greater than 11,1 kVA. This document does not apply to - safety aspects related to maintenance, and - trolley buses, rail vehicles and vehicles designed primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT SANS 62840-2:XXXXX Ed 1 Electric vehicle battery swap system -Part 2: Safety requirements. This part of IEC 62840 provides the safety requirements for a battery swap system, for the purposes of swapping swappable battery system (sbs) of electric vehicles. The battery swap system is intended to be connected to the supply network. The powere supply is uo to 1 000 V AC or up to 1 500 V d.c, in accordance with IEC 60038. This standard also applies to battery swap systems supplied from on-site storage systems (e.g. buffer batteries). Aspects covered in this standard: • Safety requirements of the battery swap system and/or its systems;			
- requirements for flush mounted primary device, - requirements for MF-WPT systems for heavy duty vehicle, and - requirements for MF-WPT systems with inputs greater than 11,1 kVA. This document does not apply to - safety aspects related to maintenance, and - trolley buses, rail vehicles and vehicles designed primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT SANS 62840-2:XXXXX Ed 1 Electric vehicle battery swap system -Part 2: Safety requirements. This part of IEC 62840 provides the safety requirements for a battery swap system, for the purposes of swapping swappable battery system (sbs) of electric vehicles. The battery swap system is intended to be connected to the supply network. The powere supply is uo to 1 000 V AC or up to 1 500 V d.c, in accordance with IEC 60038. This standard also applies to battery swap systems supplied from on-site storage systems (e.g. buffer batteries). Aspects covered in this standard: • Safety requirements of the battery swap system and/or its systems;			
- requirements for MF-WPT systems for heavy duty vehicle, and - requirements for MF-WPT systems with inputs greater than 11,1 kVA. This document does not apply to - safety aspects related to maintenance, and - trolley buses, rail vehicles and vehicles designed primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT SANS 62840-2:XXXXX Ed 1 Electric vehicle battery swap system -Part 2: Safety requirements. This part of IEC 62840 provides the safety requirements for a battery swap system, for the purposes of swapping swappable battery system (sbs) of electric vehicles. The battery swap system is intended to be connected to the supply network. The powere supply is uo to 1 000 V AC or up to 1 500 V d.c, in accordance with IEC 60038. This standard also applies to battery swap systems supplied from on-site storage systems (e.g. buffer batteries). Aspects covered in this standard: ■ Safety requirements of the battery swap system and/or its systems;			
- requirements for MF-WPT systems with inputs greater than 11,1 kVA. This document does not apply to - safety aspects related to maintenance, and - trolley buses, rail vehicles and vehicles designed primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT SANS 62840-2:XXXXX Ed 1 Electric vehicle battery swap system -Part 2: Safety requirements. This part of IEC 62840 provides the safety requirements for a battery swap system, for the purposes of swapping swappable battery system (sbs) of electric vehicles. The battery swap system is intended to be connected to the supply network. The powere supply is uo to 1 000 V AC or up to 1 500 V d.c, in accordance with IEC 60038. This standard also applies to battery swap systems supplied from on-site storage systems (e.g. buffer batteries). Aspects covered in this standard: ■ Safety requirements of the battery swap system and/or its systems;			
This document does not apply to - safety aspects related to maintenance, and - trolley buses, rail vehicles and vehicles designed primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT SANS 62840-2:XXXXX Ed 1 Electric vehicle battery swap system -Part 2: Safety requirements. This part of IEC 62840 provides the safety requirements for a battery swap system, for the purposes of swapping swappable battery system (sbs) of electric vehicles. The battery swap system is intended to be connected to the supply network. The powere supply is uo to 1 000 V AC or up to 1 500 V d.c, in accordance with IEC 60038. This standard also applies to battery swap systems supplied from on-site storage systems (e.g. buffer batteries). Aspects covered in this standard: • Safety requirements of the battery swap system and/or its systems;			
- trolley buses, rail vehicles and vehicles designed primarily for use off-road. NOTE The terms used in this document are specifically for MF-WPT SANS 62840-2:XXXXX Ed 1 Electric vehicle battery swap system -Part 2: Safety requirements. This part of IEC 62840 provides the safety requirements for a battery swap system, for the purposes of swapping swappable battery system (sbs) of electric vehicles. The battery swap system is intended to be connected to the supply network. The powere supply is uo to 1 000 V AC or up to 1 500 V d.c, in accordance with IEC 60038. This standard also applies to battery swap systems supplied from on-site storage systems (e.g. buffer batteries). Aspects covered in this standard: • Safety requirements of the battery swap system and/or its systems;		This document does not apply to	
NOTE The terms used in this document are specifically for MF-WPT SANS 62840-2:XXXXX Ed 1 Electric vehicle battery swap system -Part 2: Safety requirements. This part of IEC 62840 provides the safety requirements for a battery swap system, for the purposes of swapping swappable battery system (sbs) of electric vehicles. The battery swap system is intended to be connected to the supply network. The powere supply is uo to 1 000 V AC or up to 1 500 V d.c, in accordance with IEC 60038. This standard also applies to battery swap systems supplied from on-site storage systems (e.g. buffer batteries). Aspects covered in this standard: • Safety requirements of the battery swap system and/or its systems;			
SANS 62840-2:XXXXX Ed 1 Electric vehicle battery swap system -Part 2: Safety requirements. This part of IEC 62840 provides the safety requirements for a battery swap system, for the purposes of swapping swappable battery system (sbs) of electric vehicles. The battery swap system is intended to be connected to the supply network. The powere supply is uo to 1 000 V AC or up to 1 500 V d.c, in accordance with IEC 60038. This standard also applies to battery swap systems supplied from on-site storage systems (e.g. buffer batteries). Aspects covered in this standard: • Safety requirements of the battery swap system and/or its systems;			
IEC 62840 provides the safety requirements for a battery swap system, for the purposes of swapping swappable battery system (sbs) of electric vehicles. The battery swap system is intended to be connected to the supply network. The powere supply is uo to 1 000 V AC or up to 1 500 V d.c, in accordance with IEC 60038. This standard also applies to battery swap systems supplied from on-site storage systems (e.g. buffer batteries). Aspects covered in this standard: • Safety requirements of the battery swap system and/or its systems;	SANS 62840-2:XXXXX		2025-10-28
battery swap system is intended to be connected to the supply network. The powere supply is uo to 1 000 V AC or up to 1 500 V d.c, in accordance with IEC 60038. This standard also applies to battery swap systems supplied from on-site storage systems (e.g. buffer batteries). Aspects covered in this standard: • Safety requirements of the battery swap system and/or its systems;		IEC 62840 provides the safety requirements for a battery swap system, for the	
powere supply is uo to 1 000 V AC or up to 1 500 V d.c, in accordance with IEC 60038. This standard also applies to battery swap systems supplied from on-site storage systems (e.g. buffer batteries). Aspects covered in this standard: • Safety requirements of the battery swap system and/or its systems;			
IEC 60038. This standard also applies to battery swap systems supplied from on-site storage systems (e.g. buffer batteries). Aspects covered in this standard: • Safety requirements of the battery swap system and/or its systems;			
on-site storage systems (e.g. buffer batteries). Aspects covered in this standard: • Safety requirements of the battery swap system and/or its systems;			
 Safety requirements of the battery swap system and/or its systems; 			
Security requirements for communication			
		Security requirements for communication	

	Electromagnetic compatibility (EMC)	
	Signs and instructions	
	Protection against electric shock and other hazards This is a second of the control of the	
	This standard is applicable to battery swap systems for EV equipped with one or	
	more SBS.	
	NOTE Battery swap systems for light EVs according to the IEC 61851-3 series1	
	are under consideration. This standard is not applicable to:	
	• aspects related to maintenance and service of the battery swap station (BSS);	
	• trolley buses, rail vehicles and vehicles designed primarily for use off-road;	
CANIC (2040 2.VVVVV	maintenance and service of EVs. Electric vehicle battery swap system - Part 3: Particular Safety and	2025 10 20
SANS 62840-3:XXXXX Ed 1	interoperability requirements for battery swap systems operating with	2025-10-28
Ed I		
	removable RESS/battery systems. This standard applies to battery swap systems for removable RESS of electric road vehicle when connected to the supply	
	network, with a rated supply voltage up to 480 V AC or up to 400 V DC, for	
	battery systems with a rated voltage up to 120 V DC. This document applies to	
	battery swap systems for removable RESS/EV where the removable RESS/EV	
	is stored for the purpose of transfer power between the battery swap station and removable RESS/EV. Requirements for bidirectional energy transfer DC to AC	
	are under consideration and are not part of this document. This document	
	applies to: battery swap systems supplied from on-site storage systems (for	
	example buffer batteries etc); manual, mechanically assisted and automatic	
	systems; battery swap systems intended to supply removable battery systems	
	having communication allowing to identify the battery system characteristics;	
	battery swap systems intended to be installed at an altitude of up to 2 000 m.	
SANS 63110-1:XXXXX	Protocol for management of electric vehicles charging and discharging	2025-10-28
Ed 1	infrastructures -Part 1: Basic definitions, use cases and architectures. This	2023-10-20
Da i	standard covers the definitions, use cases and architecture for the management	
	of electric vehicle charging and discharging infrastructures. It addresses the	
	general requirements for the establishment of an e-mobility eco-system,	
	therefore covering the communication flows between different e-mobility actors	
	as well as data flows with the electric power system. This document covers the	
	following features: management of energy transfer (e.g., charging session),	
	reporting, including information exchanges related to the required energy, grid	
	usage, contractual data, and metering data; asset management of EVSE,	
	including controlling, monitoring, maintaining, provisioning, firmware update	
	and configuration (profiles) of EVSE; authentication/authorization/payment of	
	charging and discharging sessions, including roaming, pricing, and metering	
	information; the provision of other e-mobility services; cybersecurity.	
SANS 63119-2:XXXXX	Information exchange for electric vehicle charging roaming service -Part 2:	2025-10-28
Ed 1	<i>Use cases.</i> This standard specifies roaming use cases of information exchange	
	between EV	
	charging service providers (CSP), charging station operators (CSOs) and	
	clearing house platforms through roaming endpoints. The elementary use cases	
	defined in this document are designed to support the user to have access to the	
	EV supply equipment which does not belong to the home-CSP.	
SANS 10089-3:20XX	The petroleum industry Part 3: The installation, modification, and	2025-10-28
Ed 5	decommissioning of underground storage tanks, pumps/dispensers and	
	pipework at service stations and consumer installations. This standard covers	
	provisions for the installation of underground storage tanks of individual	
	capacity not exceeding 85 000 m3, pumps/dispensers and pipework at service	
	stations and consumer installations.	
SANS 17575-1:20XX	Electronic fee collection - Application interface definition for autonomous	2025-10-28
Ed 1	systems Part 1: Charging	
SANS 19167:20xx	Application of ubiquitous public access to-geographic information to an air	2025-10-28
Ed 1	quality information service. This standard facilitates an understanding of the	
	Ubiquitous Public Access (UPA) context information model, as defined in ISO	
	19154, to establish a UPA-to-Geographic Information (GI) environment. In	
	addition, this document illustrates how the UPA context information model is	
	designed and implemented to provide an air quality information service from a	
	geographic information system (GIS)-based air quality information system.	

SANS 15963-1:20xx Ed 3	Information technology - Radio frequency identification for item management - Part 1: Unique identification for RF tags numbering systems. This standard describes numbering systems that are available for the identification of RF tags and assigns various allocation classes to various agencies that issue manufacturer codes.	2025-10-28
SANS 17575-2:20XX Ed 1	Electronic fee collection - Application interface definition for autonomous systems - Part 2: Communication and connection to the lower layer. This standard defines how to convey all or parts of the data element structure defined in other parts of ISO 17575 over any communication stack and media suitable for this application.	2025-10-28
SANS 29100:20xx Ed 2	Information technology - Security techniques - Privacy framework. This standards provides a privacy framework which: - specifies a common privacy terminology - defines the actors and their roles in processing personally identifiable information (PII) - describes privacy safeguarding considerations - provides references to known privacy principles for information technology.	2025-10-28
SANS 55000:20xx Ed 2	Asset management - Vocabulary, overview and principles. This standard defines terms and establishes principles and outcomes for asset management.	2025-10-28
SANS 56000:20xx Ed 2	Innovation management - Fundamentals and vocabulary. This standard defines terms for and establishes the fundamental concepts and principles of innovation management	2025-10-28
SANS 37001:20XX Ed 2	Anti-bribery management systems - Requirements with guidance for use. This standard establishing, implementing, maintaining, and improving an anti-bribery management system, and offers requirements and guidance for setting up systems designed to help organizations prevent, detect, and respond to bribery, as well as comply with anti-bribery laws and voluntary commitments applicable to their activities.	2025-10-28
SANS 8233:XXXX Ed 1	Standard Guide for Packaging and Labeling of Consumer Resin Cannabis Products for Sale to Adult Consumers, Legally Authorized Medical Users, and Caregivers in a Business-to-Consumer Retail Environment (Retailers). This guide is for the packaging and labeling of cannabis flowers, resins, and preparations derived therefrom for sale to adult consumers, legally authorized medical users, and care givers in a business-to-consumer/patient/caregiver retail environment and other legal distribution channels. This includes labeling of products, regardless of packaging format, that will be purchased by adults in retail dispensaries, pharmacies, or other distribution methods (for example, postal shipment).	2025-10-28
SANS 14083:20xx Ed 1	Greenhouse gases - Quantification and reporting of greenhouse gas emissions arising from transport chain operations. This standard establishes a common methodology for the quantification and reporting of greenhouse gas (GHG) emissions arising from the operation of transport chains of passengers and freight.	2025-10-28
SANS 3001-CO2-3:202X Ed 1	Civil engineering test methods - Part CO2-3: Compressive strength of hardened concrete. This standard specifies a method of determining the compressive strength of test specimens of hardened concrete. The test specimens may consist of cubes or cylinders, or cubes cut from half prisms that have been used for the determination of flexural strength (see SANS 3001-CO2-5).	2025-10-28
SANS 3001-CO2-7:202X Ed 1	Civil engineering test methods Part CO2-7: Initial drying shrinkage and wetting expansion of concrete. This standard specifies a method of determining the initial drying shrinkage and wetting expansion of specimens of freshly cast concrete. It is not applicable to matured or hardened concrete or to concrete that contains expansion-inducing agents or to precast concrete products.	2025-10-28
SANS 3001-CO2-8:202X Ed 1	Civil engineering test methods Part CO2-8: Density of hardened concrete. This standard specifies a method of determining the density of hardened concrete. The method is applicable to all types of as-received, saturated and oven-dried concrete.	2025-10-28
SANS 3001-CO2-6:20XX Ed 1	Civil engineering test methods Part CO2-6: Tensile splitting strength of hardened concrete. This standard describes a method of determining the tensile splitting strength of cylindrical, cubical, and prismatic test specimens of	2025-10-28

	hardened concrete.	
SANS 3001-CO2-10:202X Ed 1	Civil engineering test methods Part CO2-10: Mortar tests - Initial drying shrinkage and wetting expansion of mortar. This standard Specifies a method of determining the initial drying shrinkage and wetting expansion of freshly mixed mortar and cast mortar specimens prepared either on site from mortar actually being used in practice or from mortar prepared in the laboratory with materials and in the proportions intended to be used.	2025-10-28
SANS 3001-CO2-9:202X Ed 1	Civil engineering test methods Part CO2-9: Mortar tests - Compressive strength of mortar. This standard specifies a method of determining the compressive strength of freshly mixed mortar and cast mortar specimens prepared either on site from mortar actually being used in practice or from mortar prepared in the laboratory with materials and in the proportions intended to be used.	2025-10-28
SANS 3001-CO2-1:202X Ed 1	Civil engineering test methods - Part CO2-1: Dimensions, tolerances and uses of cast test specimens. This standard specifies a method of ensuring that the nominal dimensions and shape of cast concrete test specimens in the form of cubes, cylinders, or rectangular prisms of square cross-section are suitable for their intended use.	2025-10-28
SANS 3001-CO2-5:202X Ed 1	Civil engineering test methods Part CO2-5: Flexural strength of hardened concrete. This standard specifies two methods of determining the flexural strength of hardened concrete: a) the two-point loading method that produces a constant bending moment along the central part of the test specimen, which is the standard method; and b) the centre-point loading method, which is an alternative method. NOTE The centre-point loading method is likely to give higher values for the flexural strength than the two-point loading method.	2025-10-28
SANS 24748-2:20XX Ed 2	Systems and software engineering - Life cycle management - Part 2: Guidelines for the application of ISO/IEC/IEEE 15288 (System life cycle processes). This standard addresses the application of system, life cycle, organizational, project, process, and conformance and adaption concepts, principally through references to ISO/IEC/IEEE 24748-1 and ISO/IEC/IEEE 15288	2025-10-28

SCHEDULE A.1: AMENDMENT OF EXISTING STANDARDS

The following draft amendments are hereby issued for public comments in compliance with the norm for the development of the South African National Standards in terms of section 23(2)(a) (ii) of the Standards Act.

Draft Standard No. and Edition	Title	Scope of amendment	Closing Date
SANS 1449: XXXX Ed 2.3	Ceramic wall and floor tiles	Amended to update the requirements for Abrasion-testing machine and to delete the annex on notes to purchasers.	2025-10-28
SANS 1522: 20XX Ed 2.3	Fire extinguishing powders	Amended to include additional requirements and to update the analysis of the monoammonium phosphate content.	2025-10-28
SANS 564: 20XX Ed 1.2	Rubber insertion sheeting	Amended to delete the annex on notes to purchasers.	2025-10-28
SANS 580: 20XX Ed 1.3	Chloroprene rubber sheet (for waterproofing)	Amended to delete the annex/appendix on notes to purchasers.	2025-10-28
SANS 938:20xx Ed 1.4	Unpolished twines	Amended to update referenced standards, and to delete the appendix on notes to purchasers.	2025-10-28
SANS 1292: XXXX Ed 1.3	Castors for furniture	Amended to delete the appendix on notes to purchasers	2025-10-28
SANS 1318:20XX Ed 1.2	Scholastic stationery	Amended to update requirements on grammage in table 1 and table 2, delete bursting strength in table 2 and update type of cover in table 4.	2025-10-28
SANS 1446:20XX Ed 1.4	Glass rovings.	Amended to delete the appendix on notes to purchasers.	2025-10-28

No. 53304 **119**

SANS 1385: XXXX	Kitchen cupboards: Built-in and free-	Amended to delete the appendix on notes to	2025-10-28
Ed 1.6	standing	purchasers.	
SANS 564:20XX	Rubber insertion sheeting	amended to delete the appendix on notes to	2025-10-28
Ed 1.2		purchasers.	
SANS 60317-8:20xx	Specifications for particular types of	Amended to update referenced standards as	2025-10-28
Ed 2.1	winding wires Part 8: Polyesterimide	they relate to the clause on electrical	
	enamelled round copper wire, class	resistance, and on resistance to refrigerants,	
	180	as well as to modify the clause on terms,	
		definitions and general notes on methods of	
		test and appearance, and on resistance to	
		transformer oil.	
SANS 60317-15:20xx	Specifications for particular types of	Amended to update referenced standards, the	2025-10-28
Ed 1.1	winding wires -Part 15:	clause on terms, definitions, general notes,	
	Polyesterimide enamelled round	111 / 1	
	aluminium wire, class 180	for electrical resistance, and for resistance to	
		transformer oil.	
SANS 911: XXXX	Natural fibre ropes	Amended to update referenced standards and	2025-10-28
Ed 3.4		to delete annex on notes to purchasers.	
SANS 3001-AS2:202X	Civil engineering test methods Part	Amended to update the introduction, to	2025-10-28
Ed 1.1	AS2: Determination of Marshall	modify the procedure and calculations.	
	stability, flow and quotient		
SANS 871:202x	Boron timber preservatives	Amended to update referenced standards,	2025-10-28
Ed 2.2		and to delete the notes to purchasers	
SANS 2084: XXXX	Menstrual cups	Amended to change title and update	2025-10-28
Ed 1.1		requirements on biocompatability.	

For access to these draft standards, visit https://www.sabs.co.za/Standards-Development/draft/drafts.asp

Should you wish to comment on the above documents, please send your comments to Dsscomments@sabs.co.za

Copies of the standards mentioned in this notice can be obtained from the Head Office of the South African Bureau of Standards at 1 Dr Lategan Road, Groenkloof, Private Bag X191, Pretoria 0001.